FIG.1
PRIOR ART

CLIENT

SERVER

OID, Rc, g^x

HASHs, Rs, Ee(IDs), g^y

Ee(IDc), HASHc

$e = prf$ (SHARED KEY, Rs, Rc, g^{xy}.)

HASHc $= prf$ (SHARED KEY, Rs, Rc, g^x, g^y, IDc)

HASHs $= prf$ (SHARED KEY, Rs, Rc, g^x, g^y, IDs)

FIG.2

SERVER 40

- INPUT UNIT 42
- RANDOM NUMBER Q GENERATOR 44
- DATA-FOR-AUTHENTICATION COMPUTING UNIT 48
- VERIFICATION UNIT 50
- MEMORY 46
- NG 54
- OK 52
- COMMUNICATION I/F 60

NETWORK 32

CLIENT 10

- INPUT UNIT 12
- RANDOM NUMBER R GENERATOR 14
- DATA-FOR-AUTHENTICATION COMPUTING UNIT 18
- VERIFICATION UNIT 20
- MEMORY 16
- NG 24
- OK 22
- COMMUNICATION I/F 30

FIG.3

```
                    ┌──────────────┐
                    │    START     │
                    └──────┬───────┘
                           │
           ┌───────────────┴────────────────┐  ┌─ 100
           │   STORE INITIAL VALUE           │
           │   (HOLD PRIVATE KEY)            │
           └───────────────┬────────────────┘
                           │
           ┌───────────────┴────────────────┐  ┌─ 110
           │ CLIENT :                        │
           │   SEND AUTHENTICATION DATA      │
           └───────────────┬────────────────┘
                           │
           ┌───────────────┴────────────────┐  ┌─ 120
           │ SERVER :                        │
           │   RECEIVE AUTHENTICATION DATA   │
           │   SEND NEW AUTHENTICATION DATA  │
           │   (UPDATE PRIVATE KEY)          │
           └───────────────┬────────────────┘
                           │
           ┌───────────────┴────────────────┐  ┌─ 130
           │ CLIENT :                        │
           │   RECEIVE AUTHENTICATION DATA   │
           │   SEND NEW AUTHENTICATION DATA  │
           │   (UPDATE PRIVATE KEY)          │
           └───────────────┬────────────────┘
                           │
                      ╱────┴────╲              ┌─ 140
              N      ╱  EXECUTED  ╲
          ┌────────╱ PREDETERMINED ╲
          │        ╲   NUMBER       ╱
          │         ╲  OF TIMES ?  ╱
          │          ╲────┬───────╱
          │               │ Y
          │   ┌───────────┴────────────────┐  ┌─ 150
          │   │ SERVER & CLIENT :          │
          │   │   AUTHENTICATION PROCESS   │
          │   └───────────┬────────────────┘
          │               │
          │        ┌──────┴───────┐
          │        │     END      │
          │        └──────────────┘
```

FIG.4

FIG.5

FIG.6

FIG.7

CLIENT

CPU — 21

24 — INPUT UNIT

STORAGE UNIT — 23

STORAGE MEDIUM

23a

22 — RAM

25 — DISPLAY UNIT

COMMUNICATION UNIT — 26

20

NETWORK

FIG.8

FIG.9

CLIENT

SERVER

P1

$\mathrm{SIGNAL}_{n,1}$
$E_{kn-1}(g^{xn}, ID_C, ID_S, SIGNAL_{n,1})$

P2

DETERMINE VALIDITY OF CLIENT

P3

$\mathrm{SIGNAL'}_{n,1}, g^{yn}$
$h(K_n ID_C, ID_S, SIGNAL'_{n,1})$

P4

DETERMINE VALIDITY OF SERVER

FIG.10

SERVER

KEY [0 | Rs] [0 | Rc] ⇧ K1

S13

SIGNALs1=prf(K1,Rc)

GENERATE Rs

⇧ K2

S17

VERIFY SIGNALc2

VERIFY Rc +Rs

S12

SIGNALc1
E(K1, RC)

S14

SIGNALs1
R0 + RC
E(K1, Rs)

S16

SIGNALc2
Rc + Rs

CLIENT

KEY [0 | 0] ⇧ K1

S11

SIGNALc1=prf(K1,R0)

GENERATE Rc

[0 | Rs] [0 | Rc] ⇧ K2

S15

SIGNALc2=prf(K2,Rs,Rc)

VERIFY SIGNALs1

VERIFY R0 +Rc

FIG.11

SERVER

S27
VERIFY SIGNALc2
VERIFY Rc +Rs

S23
SIGNALs1=prf(K,Rc)
GENERATE Rs

SIGNALs1
R0 + Rc
E(K, Rs)

S24

S22

SIGNALc1
E(K, Rc)

S26

SIGNALc2
Rc + Rs

CLIENT

S25
SIGNALc2=prf(K,Rs,Rc)
VERIFY SIGNALs1
VERIFY R0 +Rc

S21
SIGNALc1=prf(K,R0)
GENERATE Rc

FIG.12

SERVER

KEY $\boxed{R_{ci-1}} \boxed{R_{si-1}}$ ⇧ K_i

VERIFY SIGNAL$_{ci}$

VERIFY ID$_C$, ID$_S$

GENERATE R$_{si}$

SIGNAL$_{si}$ = prf(K$_i$, R$_{ci}$, R$_{si-1}$)

$\boxed{R_{ci}} \boxed{R_{si}}$ ⇧ K_{i+1}

S33

S32

SIGNAL$_{ci}$
E$_{Ki}$(ID$_C$, ID$_S$, R$_{ci}$)

SIGNAL$_{si}$
E$_{Ki}$(ID$_S$, ID$_C$, R$_{si}$)

S34

CLIENT

KEY $\boxed{R_{ci-1}} \boxed{R_{si-1}}$ ⇧ K_i

SIGNAL$_{ci}$ = prf(K$_i$, R$_{ci-1}$, R$_{si-1}$)

GENERATE R$_{ci}$

S31

$\boxed{R_{ci}} \boxed{R_{si}}$ ⇧ K_{i+1}

VERIFY SIGNAL$_{si}$

VERIFY ID$_C$, ID$_S$

S35

FIG.13

KEY : K

SERVER

VERIFY SIGNAL$_{ci}$

VERIFY ID$_C$, ID$_S$

GENERATE R$_{si}$ SIGNAL$_{si}$ = prf(K,R$_{ci}$,R$_{si-1}$)

$\begin{array}{|c|} \hline R_{ci-1} \\ \hline R_{si-1} \\ \hline \end{array}$ ⇧ S43

| SIGNAL$_{si}$ |
| E$_K$(ID$_S$, ID$_C$, R$_{si}$) | S44

$\begin{array}{|c|} \hline R_{ci} \\ \hline R_{si} \\ \hline \end{array}$ ⇧

S42

| SIGNAL$_{ci}$ |
| E$_K$(ID$_C$, ID$_S$, R$_{ci}$) |

CLIENT

KEY : K

$\begin{array}{|c|} \hline R_{ci-1} \\ \hline R_{si-1} \\ \hline \end{array}$ ⇧ S41

SIGNAL$_{ci}$ = prf(K,R$_{ci-1}$,R$_{si-1}$)

GENERATE R$_{ci}$

$\begin{array}{|c|} \hline R_{ci} \\ \hline R_{si} \\ \hline \end{array}$

VERIFY SIGNAL$_{si}$ ⇧ S45

VERIFY ID$_C$, ID$_S$

FIG.14

CLIENT

h, P

SERVER

$h, h^2(P \oplus n), n$

S51: ID_C →

S52: n ←

S53:
$C_1 = h(P \oplus n) \oplus h^2(P \oplus n)$
$C_2 = h^2(P \oplus (n+1)) \oplus h(P \oplus n)$
$C_3 = h^3(P \oplus (n+1))$

S54: C_1, C_2, C_3 →

S55: BASED ON C1, C2, AND C3, CHECK VALIDITY OF CLIENT

UPDATE INFORMATION FOR VERIFICATION AND COMMUNICATION NUMBER OF TIMES

FIG.15

CLIENT

h, P

SERVER

$h, h^2(P \oplus n), n$

S61 ID_c →

S62 n →

S63
$C_1 = h(P \oplus n) \oplus h^2(P \oplus n)$
$C_2 = h^2(P \oplus (n+1)) \oplus h(P \oplus n)$
$C_3 = h^3(P \oplus (n+1))$
$SIGNAL_n = h(h^2(P \oplus n), n)$

S64 C_1, C_2, C_3 $SIGNAL_n$ →

S65

VERIFY $SIGNAL_n$

BASED ON C1, C2, AND C3, CHECK VALIDITY OF CLIENT

UPDATE INFORMATION FOR VERIFICATION AND SESSION NUMBER OF TIMES

FIG.16

CLIENT

h, P, n

$C_1 = h(P \oplus n) \oplus h^2(P \oplus n)$

$C_2 = h^2(P \oplus (n+1)) \oplus h(P \oplus n)$

$C_3 = h^3(P \oplus (n+1))$

$SIGNAL_n = h(h^2(P \oplus n), n)$ S63

C_1, C_2, C_3

$SIGNAL_n$ S64

SERVER

$h, h^2(P \oplus n), n$

VERIFY $SIGNAL_n$ S65

BASED ON C1, C2, AND C3, CHECK VALIDITY OF CLIENT

UPDATE INFORMATION FOR VERIFICATION AND SESSION NUMBER OF TIMES